

**Diesel Reference Fuel U-21**

Version 5.3

Revision Date 2015-04-15

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product information**

Product Name : Diesel Reference Fuel U-21
Material : 1108915, 1024281, 1024280, 1032195, 1024277, 1024279,
1024278

Use : Reference Fuel

Company : Chevron Phillips Chemical Company LP
Specialty Chemicals
10001 Six Pines Drive
The Woodlands, TX 77380

Emergency telephone:**Health:**

866.442.9628 (North America)

1.832.813.4984 (International)

Transport:

North America: CHEMTREC 800.424.9300 or 703.527.3887

Asia: +800 CHEMCALL (+800 2436 2255) China:+86-21-22157316

EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)

South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group
E-mail address : SDS@CPChem.com
Website : www.CPChem.com

SECTION 2: Hazards identification**Classification of the substance or mixture**

This product has been classified in accordance with the hazard communication standard 29 CFR 1910.1200; the SDS and labels contain all the information as required by the standard.

Emergency Overview**Danger**

Physical state: Liquid **Color:** Yellow **Odor:** Stench

OSHA Hazards : Flammable Liquid, Carcinogen, Moderate skin irritant, Moderate eye irritant, Target Organ Effects

Classification

: Flammable liquids , Category 3
Skin irritation , Category 2

Diesel Reference Fuel U-21

Version 5.3

Revision Date 2015-04-15

Eye irritation , Category 2A
 Carcinogenicity , Category 1B
 Specific target organ systemic toxicity - single exposure ,
 Category 3 , Respiratory system
 Specific target organ systemic toxicity - repeated exposure ,
 Category 1 , Eyes, Blood
 Specific target organ systemic toxicity - repeated exposure ,
 Category 2 , Liver, thymus gland, Auditory organs
 Specific target organ systemic toxicity - repeated exposure ,
 Category 2 , Inhalation , Auditory organs
 Aspiration hazard , Category 1

Labeling

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H226: Flammable liquid and vapor.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H335: May cause respiratory irritation.
 H350: May cause cancer.
 H372: Causes damage to organs (Eyes, Blood, Liver, thymus gland, Auditory organs) through prolonged or repeated exposure.
 H373: May cause damage to organs (Auditory organs) through prolonged or repeated exposure if inhaled.

Precautionary Statements

: **Prevention:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe dust/fume/gas/mist/vapor/spray.
 P264 Wash skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ eye protection/ face protection.
 P281 Use personal protective equipment as required.
Response:
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Diesel Reference Fuel U-21

Version 5.3

Revision Date 2015-04-15

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P313 IF exposed or concerned: Get medical advice/attention.
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/attention.
 P337 + P313 If eye irritation persists: Get medical advice/attention.
 P362 Take off contaminated clothing and wash before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity:**IARC**

Group 2B: Possibly carcinogenic to humans

Light Aromatic Solvent 64742-95-6

Naphtha

Naphtha (petroleum), heavy catalytic reformed 64741-68-0

Ethylbenzene 100-41-4

Light Cycle Oil 64741-59-9

Naphthalene 91-20-3

Cumene 98-82-8

NTP

Reasonably anticipated to be a human carcinogen

Naphthalene 91-20-3

ACGIH

Confirmed animal carcinogen with unknown relevance to humans

Distillates (petroleum), 64742-47-8

Hydrotreated light

Light Aromatic Solvent 64742-95-6

Naphtha

Solvent Naphtha 64742-94-5

(Petroleum), Heavy Aromatic

SECTION 3: Composition/information on ingredients

Synonyms : Diesel Reference Fuel U

Molecular formula : Mixture

Component	CAS-No.	Weight %
Distillates (petroleum), Hydrotreated light	64742-47-8	100
Aromatic hydrocarbons, C9-11	70693-06-0	30 - 50

Diesel Reference Fuel U-21

Version 5.3

Revision Date 2015-04-15

Light Aromatic Solvent Naphtha	64742-95-6	20 - 30
Solvent Naphtha (Petroleum), Heavy Aromatic	64742-94-5	20 - 30
1,2,4-Trimethylbenzene	95-63-6	10 - 20
Ethylbenzene	100-41-4	10 - 20
Light Cycle Oil	64741-59-9	10 - 20
Benzene, dimethyl-	1330-20-7	1 - 10
Naphthalene	91-20-3	1 - 10
1,3,5-Trimethylbenzene	108-67-8	1 - 10
1,2,3-trimethylbenzene	526-73-8	1 - 10
Cumene	98-82-8	1 - 10

SECTION 4: First aid measures

- General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Material may produce a serious, potentially fatal pneumonia if swallowed or vomited.
- If inhaled : If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5: Firefighting measures

- Flash point : 44 °C (111 °F)
Method: Tag closed cup
- Autoignition temperature : No data available
- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.
- Unsuitable extinguishing media : High volume water jet.
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case

Diesel Reference Fuel U-21

Version 5.3

Revision Date 2015-04-15

- of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
- Hazardous decomposition products : Carbon oxides.

SECTION 6: Accidental release measures

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

Storage

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

Diesel Reference Fuel U-21

Version 5.3

Revision Date 2015-04-15

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters****US**

Ingredients	Basis	Value	Control parameters	Note
Distillates (petroleum), Hydrotreated light	OSHA Z-1	TWA	500 ppm, 2,000 mg/m3	(b),
	OSHA Z-1-A	TWA	400 ppm, 1,600 mg/m3	
	ACGIH	TWA	200 mg/m3	P, A3, Skin, varies,
Light Aromatic Solvent Naphtha	OSHA Z-1	TWA	500 ppm, 2,000 mg/m3	(b),
	OSHA Z-1-A	TWA	400 ppm, 1,600 mg/m3	
	ACGIH	TWA	200 mg/m3	P, A3, Skin, varies,
Solvent Naphtha (Petroleum), Heavy Aromatic	OSHA Z-1	TWA	500 ppm, 2,000 mg/m3	(b),
	ACGIH	TWA	200 mg/m3	P, A3, Skin, varies,
	OSHA Z-1-A	TWA	400 ppm, 1,600 mg/m3	
1,2,4-Trimethylbenzene	NIOSH REL	TWA	25 ppm, 125 mg/m3	
	ACGIH	TWA	25 ppm,	
	OSHA Z-1	TWA	100 ppm, 435 mg/m3	(b),
Ethylbenzene	OSHA Z-1-A	TWA	100 ppm, 435 mg/m3	
	OSHA Z-1-A	STEL	125 ppm, 545 mg/m3	
	ACGIH	TWA	20 ppm,	
Benzene, dimethyl-	OSHA Z-1	TWA	100 ppm, 435 mg/m3	(b),
	ACGIH	TWA	100 ppm,	BEI, A4,
	ACGIH	STEL	150 ppm,	BEI, A4,
Naphthalene	OSHA Z-1-A	STEL	150 ppm, 655 mg/m3	
	OSHA Z-1-A	TWA	100 ppm, 435 mg/m3	
	ACGIH	TWA	10 ppm,	(), A4, Skin,
1,3,5-Trimethylbenzene	ACGIH	STEL	15 ppm,	(), A4, Skin,
	OSHA Z-1	TWA	10 ppm, 50 mg/m3	(b),
	OSHA Z-1-A	TWA	10 ppm, 50 mg/m3	
1,2,3-trimethylbenzene	OSHA Z-1-A	STEL	15 ppm, 75 mg/m3	
	NIOSH REL	TWA	25 ppm, 125 mg/m3	
	NIOSH REL	TWA	25 ppm, 125 mg/m3	
Cumene	ACGIH	TWA	50 ppm,	
	OSHA Z-1	TWA	50 ppm, 245 mg/m3	X, (b),
	OSHA Z-1-A	TWA	50 ppm, 245 mg/m3	X,

- (i) Adopted values or notations enclosed are those for which changes are proposed in the NIC
 (b) The value in mg/m3 is approximate.
 A3 Confirmed animal carcinogen with unknown relevance to humans
 A4 Not classifiable as a human carcinogen
 BEI Substances for which there is a Biological Exposure Index or Indices (see BEI® section)
 P Application restricted to conditions in which there are negligible aerosol exposures
 Skin Danger of cutaneous absorption
 varies varies
 X Skin notation

Immediately Dangerous to Life or Health Concentrations (IDLH)

Substance name	CAS-No.	Control parameters	Update
Ethylbenzene	100-41-4	Immediately Dangerous to Life or Health Concentration Value 800 parts per million	1995-03-01
Benzene, dimethyl-	1330-20-7	Immediately Dangerous to Life or Health Concentration Value 900 parts per million	1995-03-01
Naphthalene	91-20-3	Immediately Dangerous to Life or Health Concentration Value 250 parts per million	1995-03-01
Cumene	98-82-8	Immediately Dangerous to Life or Health Concentration Value 900 parts per million	1995-03-01

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits.

Diesel Reference Fuel U-21

Version 5.3

Revision Date 2015-04-15

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

- Respiratory protection : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this material if exposure to harmful levels of airborne material may occur, such as: Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection. Air-Purifying Respirator for Organic Vapors.
- Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
- Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles. Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate: Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
- Protective measures : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- Physical state : Liquid
 Color : Yellow
 Odor : Stench

Safety data

- Flash point : 44 °C (111 °F)
 Method: Tag closed cup

Diesel Reference Fuel U-21

Version 5.3

Revision Date 2015-04-15

Lower explosion limit	: No data available
Upper explosion limit	: No data available
Oxidizing properties	: No
Autoignition temperature	: No data available
Thermal decomposition	: No data available
Molecular formula	: Mixture
Molecular weight	: Not applicable
pH	: Not applicable
pour point	: No data available
Boiling point/boiling range	: 154 - 271 °C (309 - 520 °F)
Vapor pressure	: No data available
Relative density	: 0.79 at 15.6 °C (60.1 °F)
Density	: 794.5 g/l
Water solubility	: Negligible
Partition coefficient: n-octanol/water	: No data available
Viscosity, kinematic	: 2.1 cSt at 40 °C (104 °F)
Relative vapor density	: 3 (Air = 1.0)
Evaporation rate	: < 1
Percent volatile	: > 99 %

SECTION 10: Stability and reactivity

Chemical stability : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Possibility of hazardous reactions

Conditions to avoid : Heat, flames and sparks.

Materials to avoid : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Diesel Reference Fuel U-21

Version 5.3

Revision Date 2015-04-15

Thermal decomposition : No data available

Hazardous decomposition products : Carbon oxides

Other data : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**Diesel Reference Fuel U-21**

Acute oral toxicity : LD50: > 5,000 mg/kg
Species: rat
Method: Acute toxicity estimate

Diesel Reference Fuel U-21

Acute inhalation toxicity : LC50: > 20 mg/l
Exposure time: 4 h
Species: rat
Test atmosphere: dust/mist
Method: Acute toxicity estimate

Diesel Reference Fuel U-21

Acute dermal toxicity : LD50: > 5,000 mg/kg
Species: rabbit
Method: Acute toxicity estimate

Diesel Reference Fuel U-21

Skin irritation : Skin irritation

Diesel Reference Fuel U-21

Eye irritation : Eye irritation.

Diesel Reference Fuel U-21

Sensitization : Does not cause sensitization.

Diesel Reference Fuel U-21

Repeated dose toxicity : Method: Based on product or component testing, long term repeated exposure may cause damage to the following organs:
Target Organs: Auditory organs, Eyes, Blood, Thymus, Liver
Estimated based on individual component values.

Diesel Reference Fuel U-21

Carcinogenicity : Method: Expected to be carcinogenic based on individual component data.

Developmental Toxicity

Distillates (petroleum), Hydrotreated light : Species: rat
Application Route: Inhalation
Dose: 0, 106, 364 mg/l

Diesel Reference Fuel U-21

Version 5.3

Revision Date 2015-04-15

	<p>Exposure time: 6h/d Test period: GD 6 - 20 NOAEL Teratogenicity: \geq 364 mg/l NOAEL Maternal: \geq 364 mg/l</p> <p>Species: rat Application Route: oral gavage Dose: 500, 1000, 1500, 2000 mg/kg/d Exposure time: 10 d Test period: GD 6 - 15 Method: OECD Guideline 414 NOAEL Teratogenicity: 1,000 mg/kg NOAEL Maternal: 500 mg/kg</p>
Aromatic hydrocarbons, C9-11	<p>Species: rat Application Route: Oral diet Dose: 0, 75, 150, 450 mg/kg/day Exposure time: GD 6-15 NOAEL Teratogenicity: $>$450 mg/kg/day NOAEL Maternal: 150 mg/kg/day</p>
Light Cycle Oil	<p>Species: rat Application Route: Dermal Dose: 0, 25, 50, 125, 250, 500, 1... Number of exposures: daily Test period: GD 0-19 NOAEL Maternal: 125 mg/kg</p>
Benzene, dimethyl-	<p>Species: rat Application Route: Inhalation Dose: 0, 805, 1610 ppm Number of exposures: 6 h/d Test period: GD 7-16 NOAEL Maternal: 1610 ppm</p> <p>Species: mouse Application Route: oral gavage Dose: 0, 780, 1960, 2619 mg/kg Number of exposures: 3 times/d Test period: GD 6-15 NOAEL Teratogenicity: 780 mg/kg NOAEL Maternal: 780 mg/kg</p>
Naphthalene	<p>Species: rabbit Application Route: oral gavage Dose: 40, 200, 400 mg/kg Test period: 29 d, GD 6-18 NOAEL Teratogenicity: 400 mg/kg</p>
Cumene	<p>Species: rat Application Route: Inhalation Dose: 0, 100, 500, 1200 ppm Number of exposures: 6 h/d Test period: GD 6-15 NOAEL Teratogenicity: $>$ 1200 ppm NOAEL Maternal: 100 ppm</p>

Diesel Reference Fuel U-21

Version 5.3

Revision Date 2015-04-15

Species: rabbit
 Application Route: Inhalation
 Dose: 0, 500, 1200, 2300 ppm
 Number of exposures: 6 h/d
 Test period: GD 6-18
 NOAEL Teratogenicity: > 2300 ppm

Diesel Reference Fuel U-21**Aspiration toxicity**

: Substances known to cause human aspiration toxicity hazards or to be regarded as if they cause human aspiration toxicity hazard.

CMR effects

Ethylbenzene

: Mutagenicity: In vivo tests did not show mutagenic effects
 Teratogenicity: Did not show teratogenic effects in animal experiments.
 Reproductive toxicity: No toxicity to reproduction

Light Cycle Oil

Carcinogenicity: Possible human carcinogen

Benzene, dimethyl-

Carcinogenicity: Limited evidence of carcinogenicity in animal studies
 Mutagenicity: Did not show mutagenic effects in animal experiments.
 Teratogenicity: Damage to fetus not classifiable

Naphthalene

Carcinogenicity: Limited evidence of carcinogenicity in animal studies

Diesel Reference Fuel U-21**Further information**

: Solvents may degrease the skin.

SECTION 12: Ecological information**Ecotoxicity effects****Toxicity to fish**

: Very toxic to fish.
 Estimated based on individual component values.

Toxicity to daphnia and other aquatic invertebrates

: LC50: < 1 mg/l
 Exposure time: 48 h
 Method: Estimated based on individual component values.

Toxicity to algae

: EC50: < 1 mg/l
 Exposure time: 96 h
 Method: Estimated based on individual component values.

Distillates (petroleum), light catalytic cracked

: 1

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

Distillates (petroleum),

: NOEC: 0.48 mg/l

Diesel Reference Fuel U-21

Version 5.3

Revision Date 2015-04-15

1,3,5-Trimethylbenzene	: Toxic to aquatic life with long lasting effects.
1,2,3-trimethylbenzene	: Toxic to aquatic life with long lasting effects.
Toxicity Data on Soil	: No data available
Other organisms relevant to the environment	: No data available
Impact on Sewage Treatment	: No data available
Results of PBT assessment Light Cycle Oil	: Non-classified PBT substance, Non-classified vPvB substance
Additional ecological information	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life., Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)
UN1202, DIESEL FUEL, 3, III

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)
UN1202, DIESEL FUEL, 3, III, (44 °C), MARINE POLLUTANT, (LIGHT CYCLE OIL, NAPHTHALENE)

Diesel Reference Fuel U-21

Version 5.3

Revision Date 2015-04-15

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

UN1202, DIESEL FUEL, 3, III

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

UN1202, DIESEL FUEL, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS, (LIGHT CYCLE OIL, NAPHTHALENE)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

UN1202, DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS, (LIGHT CYCLE OIL, NAPHTHALENE)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

UN1202, DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS, (LIGHT CYCLE OIL, NAPHTHALENE)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**National legislation**

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

CERCLA Reportable Quantity : 2000 lbs
Benzene, dimethyl-Naphthalene

SARA 302 Reportable Quantity : This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 304 Reportable Quantity : This material does not contain any components with a section 304 EHS RQ.

Diesel Reference Fuel U-21

Version 5.3

Revision Date 2015-04-15

SARA 313 Ingredients : The following components are subject to reporting levels established by SARA Title III, Section 313:

: 1,2,4-Trimethylbenzene - 95-63-6
Ethylbenzene - 100-41-4
Benzene, dimethyl- - 1330-20-7
Naphthalene - 91-20-3
Cumene - 98-82-8

Clean Air Act

Ozone-Depletion Potential : This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

: Ethylbenzene - 100-41-4
Benzene, dimethyl- - 1330-20-7
Cumene - 98-82-8

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

: Ethylbenzene - 100-41-4
Benzene, dimethyl- - 1330-20-7
Cumene - 98-82-8

US State Regulations

Pennsylvania Right To Know

: 1,2,4-Trimethylbenzene - 95-63-6
Ethylbenzene - 100-41-4
Benzene, dimethyl- - 1330-20-7
Naphthalene - 91-20-3
Cumene - 98-82-8

New Jersey Right To Know

: 1,2,4-Trimethylbenzene - 95-63-6
Ethylbenzene - 100-41-4
Benzene, dimethyl- - 1330-20-7
Naphthalene - 91-20-3
Cumene - 98-82-8

California Prop. 65
Ingredients

: WARNING! This product contains a chemical known in the State of California to cause cancer.

Diesel Reference Fuel U-21

Version 5.3


Revision Date 2015-04-15

Notification status

Europe REACH : On the inventory, or in compliance with the inventory
 United States of America TSCA : On TSCA Inventory
 Canada DSL : All components of this product are on the Canadian DSL.
 Australia AICS : On the inventory, or in compliance with the inventory
 New Zealand NZIoC : Not in compliance with the inventory
 Japan ENCS : On the inventory, or in compliance with the inventory
 Korea KECI : On the inventory, or in compliance with the inventory
 Philippines PICCS : On the inventory, or in compliance with the inventory
 China IECSC : On the inventory, or in compliance with the inventory

SECTION 16: Other information

NFPA Classification : Health Hazard: 2
 Fire Hazard: 2
 Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 664950

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure	OSHA	Occupational Safety & Health

Diesel Reference Fuel U-21

Version 5.3

Revision Date 2015-04-15

	Scenario Tool		Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		